



SINGLE-SPLIT WALL MOUNTED TYPE

Premium Series **SRK-ZS-WF**

New!



Black & White(-WFB)



Titanium(-WFT)



SRK20ZS-WF, SRK25ZS-WF,
SRK35ZS-WF, SRK50ZS-WF

Pure White(-WF)



BUILT IN WIRELESS LAN



Wireless remote control



SRC20ZS-W, SRC25ZS-W2
SRC35ZS-W2



SRC50ZS-W

KEY FEATURES

- Elegant, timeless design, best suited for small to medium sized living spaces.
- Users can choose a colour they like from three different choices.
- Low Global Warming Potential (GWP) and High energy efficiency by new refrigerant R32.
- Quiet Air Flow & Long Reach is achieved by jet technology.
- Colour variation available. Users can choose from three different choices.
- Wireless interface control included.

SPECIFICATIONS

Indoor unit			SRK20ZS-WF,-WFB,-WFT	SRK25ZS-WF,-WFB,-WFT	SRK35ZS-WF,-WFB,-WFT	SRK50ZS-WF,-WFB,-WFT			
Outdoor unit			SRC20ZS-W	SRC25ZS-W2	SRC35ZS-W2	SRC50ZS-W			
Power source			1 Phase, 220 - 240V, 50Hz						
Nominal cooling capacity (Min~Max)		kW	2.0(0.9~2.9)	2.5(0.9~3.1)	3.5(0.9~4.0)	5.0(1.3~5.5)			
Nominal heating capacity (Min~Max)		kW	2.7(0.9~4.3)	3.2(0.9~4.5)	4.0(0.9~5.0)	5.8(1.3~6.6)			
Power consumption		Cooling/Heating	kW		0.44 / 0.59	0.62 / 0.74	0.89 / 0.94	1.35 / 1.56	
EER/COP		Cooling/Heating	4.55 / 4.58		4.03 / 4.32	3.93 / 4.26	3.70 / 3.72		
Max. running current			A		9	9	9	14.5	
Sound power level	Indoor	Cooling/Heating	dB(A)		48 / 50	50 / 53	54 / 56	59 / 60	
	Outdoor	Cooling/Heating	56 / 56		56 / 58	61 / 61	61 / 63		
Sound pressure level	Indoor	Cooling (Hi/Me/Lo/Ulo)	34 / 25 / 22 / 19		36 / 28 / 23 / 19	40 / 30 / 26 / 19	46 / 36 / 29 / 22		
	Outdoor	Heating (Hi/Me/Lo/Ulo)	36 / 29 / 23 / 19		39 / 30 / 24 / 19	41 / 36 / 25 / 19	46 / 37 / 31 / 24		
Air flow	Indoor	Cooling/Heating	m ³ /min		45 / 45	46 / 46	50 / 48	51 / 52	
	Outdoor	Cooling (Hi/Me/Lo/Ulo)	9.3 / 7.0 / 5.9 / 5.0		9.9 / 8.0 / 5.9 / 5.0	11.3 / 8.7 / 7.0 / 5.0	12.1 / 9.9 / 7.4 / 5.9		
		Heating (Hi/Me/Lo/Ulo)	10.0 / 8.5 / 6.5 / 5.9		11.3 / 8.7 / 6.7 / 5.9	12.3 / 11.0 / 7.0 / 5.6	13.9 / 11.2 / 9.1 / 7.4		
		Cooling/Heating	27.4 / 23.6		27.4 / 23.6	31.5 / 27.8	32.8 / 32.8		
Exterior dimensions	Indoor	HeightxWidthxDepth	mm		290 x 870 x 230				
	Outdoor		540 x 780(+62) x 290		595 x 780(+62) x 290				
Net weight		Indoor / Outdoor	kg		9.5 / 31.0		9.5 / 34.5	10.0 / 36.0	
Refrigerant		Type/GWP	R32 / 675						
		Charge	kg/TCO ₂ Eq		0.62 / 0.419		0.78 / 0.527	1.05 / 0.709	
Refrigerant piping size		Liquid/Gas	ø mm				6.35(1/4") / 9.52(3/8")		6.35(1/4") / 12.7(1/2")
Refrigerant line (one way) length [chargeless length]			m				Max. 20 [15]		Max. 25 [15]
Vertical height differences		Outdoor is higher/lower	m				Max. 10 / Max. 10		Max. 15 / Max. 15
Outdoor operating temperature range		Cooling	°CDB				-15~46		
		Heating	-15~24						
Clean filter			Allergen Clear Filter x 1, Photocatalytic Washable Deodorising Filter x 1						

* The data are measured under the following conditions(ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

* Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

* 'tonne(s) of CO₂ equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.